

## Rotary Microtome CUT 6062

Precise full automation in modular design



### Microtomes

CUT 4062

CUT 5062

► CUT 6062

MTR

Cryostats

Paraffin

Embedding Centers

Tissue processors

Stainers

Cover slipper

Knife sharpener

Floating bath

Slide warmer

# Rotary Microtome CUT 6062

Precise full automation in modular design



Standard unit for paraffin sections and research-, plastic- and industrial applications. The fully motorised unit offers an even greater comfort than manual and semi-automatic microtomes whilst retaining all essential features of this series. Additional features are:

- ▶ *Motor drive*
- ▶ *Footswitch*
- ▶ *Emergency stop*
- ▶ *Operating pad for motorised cutting*
- ▶ *Operating pad for motorised advance / return*
- ▶ *Individual or series cutting*
- ▶ *Advance automatic in 2 speeds*
- ▶ *Specimen final position can be selected, top or bottom*
- ▶ *Specimen size up to 50 x 50 mm with standard object clamp or standard cassette size for universal cassette clamp*
- ▶ *Motorized cutting steplessly adjustable*
- ▶ *Speed for cutting and returning specimen can be adjusted seperately*
- ▶ *Universal power unit 100 – 240 V, 50/60 Hz*
- ▶ *The equipment is supplied completely useable including:*
  - *Object orientation unit alternatively fixed*
  - *Universal cassette clamp alternatively standard object clamp*
  - *Knife holder base with disposable blade holder low profile or high profile alternatively standard knife holder*
  - *Section waste tray*



*The operating pad for advance / retraction, slow motion, cutting thickness adjustment and trimming*



*CUT 4062 – manual model*



*CUT 5062 – semi-automatic model*

## Technical Data

Range of thickness	0,5 µm – 100 µm
Increments	0,5 µm from 0,5 µm – 2,0 µm 1,0 µm from 2,0 µm – 10 µm 2,0 µm from 10 µm – 50 µm 5,0 µm from 50 µm – 100 µm
Horizontal specimen advance	28 mm
Vertical stroke	60 mm
Specimen orientation	XY-Axes: 8°, Z-Axes: 360°
Cutting speed	steplessly adjustable from 3 – 300 mm/sec
Advance for trimming	adjustable from 0 – 300 µm, free programmable

## Weight and Dimensions

	Depth x Width x Height	
Dimensions (in mm)	495 x 400 x 290	
Dimensions packed (in mm)	650 x 550 x 480	
Weight net	29 kg	
Weight packed	41 kg	
Electrical parameters	Art.-No. 1080001	230 V / 50 Hz
	Art.-No. 1081001	230 V / 60 Hz
	Art.-No. 1082001	115 V / 60 Hz
	Art.-No. 1083001	100 V / 50 Hz
	Art.-No. 1084001	100 V / 60 Hz

Please ask for other units for Histopathology and consumables as well as laminar flow equipment.

Specifications are subject to change without notice

## SLEE MEDICAL GMBH

P. O. Box 10 05 07  
D-55129 Mainz · Germany

Fon +49 (0) 6131/95871-0  
Fax +49 (0) 6131/95871-0

mail@sleemainz.com  
www.sleemainz.com